

Click here to contact American Rigging Supply, Inc.

Hand Crimp Life Line Fittings were first developed by JOHNSON in 1967 after extensive testing. These fittings were designed for easy installation by the boat owner or professional. Acceptance caught on quickly in the marine trade and became widely used by OEM's and boat owners alike. The 1969 LANDS' END hardware catalog even featured our fittings. Today our fittings are still widely used in the marine and now the architectural trade. A properly installed hand crimp fitting will hold *65-70% of the breaking strength of 7x7 cable. The proper crimping tool and instructions must be used to assure a safe installation. Johnson sells two tools that can be used to crimp Johnson fittings (see page 21). Be sure to specify JOHNSON as these fittings have been copied around the world. * See note on page 21 regarding Hand Crimp terminal guidelines.

Pelican Hooks



***Snap Gate Hook - "Over Center"**

Patent Numbers DES, 421.892 US 6,237,927 B1

This is our latest and best design yet. Features the "over center" design with no load on the swinging hook when closed. This feature allows easy opening yet stays secure with split ring on the plunger latching device. Investment Cast T-316 Stainless.

26-884	1/8" wire	1/4"-28 L.H.	1-1/4" adj.
27-886	3/16" wire	5/16"-24 L.H	1-1/4" adj.

***Snap Gate Hook - Body Only**

Patent Numbers DES, 421.892 US 6,237,927 B1

For those that wish to replace their existing hooks-just match up the thread size. 3 1/2" long from end of body to inside bearing point of hook. Investment Cast T-316 Stainless.

21-80	5/16"-24 L.H.
21-80-1	5/16"-24 R.H.
21-81	1/4"-28 L.H.
21-88	8mm R.H.

Repair Kit - Snap Gate Hook

21-850 Repair Kit for lost or worn latching mechanisms

R-4 Ring Only

* Body Investment Cast in China



Mini Snap Gate Hook - "Over Center"

Our new Mini Snap Gate Hook features our same "Over-Center" design as our larger snap gate hood. This feature allows easy opening and closing with no load on the swinging hook when closed. Ideal for lower lifelines and powerboats. 2-3/4" grip length, 3" overall. Investment Cast T-316 Stainless.

26-784	1/8" wire	1/4"-28 L.H.	1" adj.
27-786	3/16" wire	1/4"-28 L.H.	1" adj.
21-76	Body Only	1/4"-28 L.H.	1" adj.



Safe Lock Gate Hook T-316

Stainless, safe, inexpensive design Practical Sailor called a "well engineered hunk of metal". Adjusts in place with knurled nut, stamped metal construction - 3 3/4" long from end of body to inside bearing point of hook.

26-404	1/8" wire	1/4"-28 L.H.	1-1/4" adj.
27-403	3/16" wire	1/4"-28 L.H.	1-1/4" adj.
35-622	Replacement Knurled Nut		



35-622

Can be had R.H. - Special Order

Replacement Terminals on Page 20



Tubular Gate Hook- T316

Inexpensive, slender tubular design with a stamped hook. 4 3/4" long from end of body to inside bearing point of hook.

26-403	1/8" wire	1/4"-28 L.H.	1 1/2" adj.
27-403	3/16" wire	1/4"-28 L.H.	1 1/2" adj.

Click here to contact American Rigging Supply, Inc.

Open Body Turnbuckle

Jaw to Hand Crimp Terminal

Classic, traditional design. Forged silicon bronze body with T-316 stainless ends.

26-314	Chrome	1/8" wire 1/4" pin	3" adj.
27-316	Chrome	3/16" wire 1/4" pin	3" adj.



Tubular Turnbuckle

Jaw to Hand Crimp Terminal - Check Nut Locking

Our most popular life line turnbuckle. Check nut locking. T-316 stainless.

26-412	1/8" wire	1/4" pin	3" adj.
27-412	3/16" wire	1/4" pin	3" adj.



Replacement Parts on Pages 19-20

Tubular Turnbuckle

Eye to Hand Crimp Turnbuckle - Check Nut Locking

Used where an eye is required for attachment instead of a jaw. Check nut locking. T-316 stainless.

26-401	1/8" wire	3" adj.
27-401	3/16" wire	3" adj.



Deck Toggle Turnbuckle

Deck Toggle to Hand Crimp Terminal

This "T" bolt style fitting is used on decks or bulkheads. Toggle nut style also available to match old style. T-316 stainless.

26-412-1T	1/8" wire	1/4"-28	3" adj.
27-412-1T	3/16" wire	1/4"-28	3" adj.



"Smooth Line" Turnbuckle

Closed Thread

Very popular architectural turnbuckle also great for life lines. No exposed threads. Cable termination is hidden inside of body and rotates on threaded cap. For details see page 5 of architectural section. T-316 stainless.

26-715	1/8" wire	1/4" pin	2" adj.
27-715	3/16" wire	1/4" pin	2" adj.

Smooth Line Replacement Parts

60-610	Nose Cone - 1/8"
60-611	Nose Cone - 3/16"
60-619+36-611	Crimp Sleeve - 1/8"
60-619	Crimp Sleeve - 3/16"



Adjuster Turnbuckle

Jaw to Hand Crimp Terminal

Stamped, strap design turnbuckle with knurled nut for adjustment. T-316 stainless/bronze construction.

26-302	1/8" wire	1/4" pin	2-3/4" adj.
27-302	3/16" wire	1/4" pin	2-3/4" adj.
35-624	Replacement Knurled Nut		



Double Hand Crimp Terminal Fitting

Used whenever two pieces of cable need to be joined.

27-415-5-6	1/8 to 3/16" Hand Crimp
------------	-------------------------



Conversion Sleeve

Allows the use of 3/16" life line fittings to be used with 1/8" cable. Slide over cable first then into fitting.

36-611	1/8 to 3/16" Hand Crimp
--------	-------------------------

Click here to contact American Rigging Supply, Inc.



Swivel, Single Gate Eye

A single eye is used on one end of the gate area to attach the gate hook.

#	26-409	1/8" wire
	27-409	3/16" wire



Threaded, Single Gate Eye

Same as above only terminal is threaded into eye nut.

#	26-407	1/8" wire
	27-407	3/16" wire



Swivel, Interlocking Gate Eye

An interlocking gate eye is used at the opposite end of the gate hook as a "hinge" for the gate.


#	26-410	1/8" wire
	27-410	3/16" wire



Threaded, Interlocking Gate Eye

Same as above only terminal is threaded into eye nut.

	26-408	1/8" wire
	27-408	3/16" wire



→ 3/4" to 1" ←

Eye to Eye Fitting

This fitting can be used wherever an eye is required on each side of the stanchion.

#	22-100	Adjustable between 3/4" and 1"
---	--------	--------------------------------



Eye to Interlocking Gate Eye

This fitting can be used wherever an eye is required on one side, and an interlocking eye on the other side of a stanchion.

#	22-304-100	Adjustable between 3/4" and 1"
---	------------	--------------------------------



Adjuster-Short

Generally used at the stern rail in conjunction with the single gate eye to tension that section of the gate.

26-406	1/8" wire 1/4" pin	1" adj.
35-620	Knurled Nut for 1/8" size	
27-406	3/16" wire 1/4" pin	1" adj.
35-621	Knurled Nut for 3/16" size	



Toggle Jaw, "T" Style

Generally used at the stern rail when no gate is required with a turnbuckle forward.

#	26-415	1/8" wire 1/4" pin
	27-415	3/16" wire 1/4" pin



Toggle Jaw, Old Style

Same as above only uses toggle nut style instead of "T" bolt style.

26-405	1/8" wire 1/4" pin
27-405	3/16" wire 1/4" pin



Deck Toggle - Old Style

This fitting can be used wherever a cable needs to be terminated to a deck or bulkhead.

26-405-1	1/8" wire "Old Style"
----------	-----------------------



Deck Toggle - 'T' Style

Same Deck Toggle only "T" bolt construction.

#	26-415-1T	1/8" wire "T-Style"
	27-415-1T	3/16" wire "T-Style"



Stanchion Terminal

Used where the cable needs to be terminated at the stanchion.

26-405-5F	1/8" wire
27-405-5F	3/16" wire

Not a true 1/8" terminal (3/16" terminal with sleeve).



All T-316 Stainless!



Hand Crimp terminals, when properly applied, are approximately 65-70% of 7 x 7 wire strength. While this has proven adequate for life lines, we do not approve use of these fittings for standing rigging or other high load applications. Instructions for attachment (sent with order) must be followed.