

*Click here to contact American Rigging Supply, Inc.*


### Rigging Toggles

These stainless steel rigging toggles are essential to prevent misalignment of rigid jaw turnbuckles. They are also used as a simple way to save rigging that was made too short. Ultimate strength exceeds the corresponding clevis pin. All sizes include pins.




#### Specifications & Data

CAT. NO.	A	B	C	D	E	F	G	SAFE WORKING LOAD
12-120	1/4"	1/4"	.094	5/16"	1"	5/16"	5/8"	1000 lbs
12-121	5/16"	5/16"	.094	19/64"	1-1/4"	11/32"	5/8"	1600 lbs
12-122	3/8"	3/8"	.141	23/64"	1-5/8"	13/32"	3/4"	2800 lbs
12-126	7/16"	7/16"	.165	27/64"	1-11/16"	15/32"	7/8"	3500 lbs
12-123	1/2"	1/2"	.187	31/64"	1-7/8"	17/32"	1"	4200 lbs
12-124	5/8"	5/8"	1/4"	39/64"	2-1/4"	11/16"	1-1/4"	5900 lbs
12-125	3/4"	3/4"	1/4"	47/64"	2-3/4"	13/16"	1-1/2"	9000 lbs



### Double Jaw Toggles

Like our Eye Jaw toggles only used to facilitate toggling action when used with marine eyes and mechanical fittings. These toggles are available in 7 sizes from 1/4" - 3/4" pin sizes. All sizes include pins.



#### Specifications & Data

CAT. NO.	A	B	C	D	E	F	G	SAFE WORKING LOAD	Upper Replacement Washer	Upper Replacement Clevis Pin w/ Cotter
12-320	1/4"	1/4"	13GA	5/8"	1/4"	1-1/16"	1/2"	1000 lbs	320W	CP-4-20c
12-321	5/16"	5/16"	13GA	3/4"	5/16"	1-1/4"	5/8"	1600 lbs	321W	CP-5-24c
12-322	3/8"	3/8"	10GA	1"	3/8"	1-1/12"	3/4"	2800 lbs	322W	CP-6-32c
12-326	7/16"	7/16"	8GA	1-1/8"	7/16"	1-3/4"	7/8"	3500 lbs	326W	CP-7-40c
12-323	1/2"	1/2"	3/16"	1-1/4"	1/2"	2"	1"	4200 lbs	323W	CP-8-40c
12-324	5/8"	5/8"	1/4"	1-1/2"	5/8"	2-1/2"	1-1/4"	5900 lbs	324W	CP-10-48c
12-325	3/4"	3/4"	1/4"	1-3/4"	3/4"	3"	1-1/2"	9000 lbs	325W	CP-12-48-1c