



Photo courtesy of Sabre Yachts



## Positive Lock Stainless Steel Tubular Turnbuckles Jaw and Jaw

Positive locking with our LOCKING RINGS. They replace expendable cotter pins and being captive, can not be lost overboard. There are no pointed or rough ends to snag sails or shins.

Replacement Parts on  
Pages 12, 42 & 43

Patent Number 4025207

**Investment Cast T-316 Stainless Steel**

### Specifications & Data

CAT. NO.	TYPE	WIRE SIZE	APPROX. BREAKING STRENGTH	SAFE WORKING LOAD	THREAD SIZE	PIN TO PIN LENGTH		BODY	PIN DIA	WT.	
						Closed	Open			lb	oz
04-120**	Jaw/Jaw	To 5/32"	2,500 lbs.	1000 lbs.	1/4-28	7-3/4"	10-5/8"	4-1/2	1/4"		5
07-110**	Jaw/Jaw	To 3/16"	4,000 lbs.	1600 lbs.	5/16-24	8-1/2"	11-5/8"	5-1/8	5/16"		8
08-110**	Jaw/Jaw	To 1/4"	7,000 lbs.	2800 lbs.	3/8-24	9-1/4"	12-1/2"	5-5/8	3/8"		13
09-100 <sup>Δ</sup>	Jaw/Jaw	To 5/16"	10,500 lbs.	4200 lbs.	1/2-20	12"	16-3/4"	7	1/2"	1	12
10-100 <sup>Δ</sup>	Jaw/Jaw	To 3/8"	14,800 lbs.	5900 lbs.	5/8-18	14"	19"	8-5/8	5/8"	3	10

\*\*Jaw with "T" Toggle Construction. All others have bronze toggle nuts to prevent galling under high load conditions.

<sup>Δ</sup> Available with Bronze Rods on special order. Add-1 to catalog number, no price increase.

See page 43 for replacement rings.

***Click here to contact American Rigging Supply, Inc.***

**Stainless Steel Tubular Turnbuckles - Jaw & Machine Swage**

Positive Locking



**Specifications & Data**

**Investment Cast T-316 Stainless Steel**

CAT. NO.	TYPE	WIRE SIZE	APPROX. BREAKING STRENGTH	SAFE WORKING LOAD	THREAD SIZE	ADJUSTMENT	BODY LENGTH	PIN DIA	WT.	
									lb	oz
04-123**	Jaw/Swage	3/32"	2,500 lbs	1000 lbs.	1/4-28	2-7/8"	4-1/2	1/4"		4
04-124**	Jaw/Swage	1/8"	2,500 lbs	1000 lbs.	1/4-28	2-7/8"	4-1/2	1/4"		4
04-125**	Jaw/Swage	5/32"	2,500 lbs	1000 lbs.	1/4-28	2-7/8"	4-1/2	1/4"		4
07-115**	Jaw/Swage	5/32"	4,000 lbs.	1600 lbs	5/16-24	3-1/8"	5-1/8	5/16"	1	7
07-116**	Jaw/Swage	3/16"	4,000 lbs.	1600 lbs	5/16-24	3-1/8"	5-1/8	5/16"	3	7
08-116**	Jaw/Swage	3/16"	7,000 lbs	2800 lbs.	3/8-24	3-1/4"	5-5/8	3/8"		11
08-117**	Jaw/Swage	7/32"	7,000 lbs	2800 lbs.	3/8-24	3-1/4"	5-5/8	3/8"		11
08-118**	Jaw/Swage	1/4"	7,000 lbs	2800 lbs.	3/8-24	3-1/4"	5-5/8	3/8"		11
09-108	Jaw/Swage	1/4"	10,500 lbs	3500 lbs.	1/2-20	4-1/8"	7	1/2"	1	9
09-109	Jaw/Swage	9/32"	10,500 lbs	3500 lbs.	1/2-20	4-1/8"	7	1/2"	1	9
09-110	Jaw/Swage	5/16"	10,500 lbs	4200 lbs.	1/2-20	4-1/8"	7	1/2"	1	9
10-110	Jaw/Swage	5/16"	14,800 lbs	4200 lbs.	5/8-18	5"	8-5/8	5/8"	3	2
10-112	Jaw/Swage	3/8"	14,800 lbs	5900 lbs.	5/8-18	5"	8-5/8	5/8"	3	2

NOTE: The 03 & 04 series come standard with L.H. upper terminal. All other series have R. H. The 04 series is available with R. H. upper terminal. To order add -12 to the catalog number.

\*\*Jaw with "T" Toggle Construction. All others have bronze toggle nuts to prevent galling under high load conditions.



photo courtesy of Island Packet Yachts



**Open Body Turnbuckles - Jaw and Jaw**

For those who prefer a traditional body turnbuckle. The forged silicon bronze body, coupled with our integral toggle jaw, provides positive locking and ease of adjustment.

Forged silicon bronze bodies with stainless ends offer a great non-galling combination. Integral toggle jaw eliminates the need for a separate rigging toggle.

**Specifications & Data**

CAT. NO.	TYPE	WIRE SIZE	APPROX. BREAKING STRENGTH	SAFE WORKING LOAD	THREAD SIZE	PIN TO PIN LENGTH		BODY LENGTH	PIN DIA	WT.	
						Closed	Open			lb	oz
42-110**	Jaw/Jaw	To 5/32"	2,500 lbs.	1000 lbs.	1/4-28	8"	11"	4-5/8	1/4"		5
43-110**	Jaw/Jaw	To 3/16"	4,000 lbs.	1600 lbs.	5/16-24	8-3/8"	12	5-1/2	5/16"		8
44-110**	Jaw/Jaw	To 1/4"	7,000 lbs.	2800 lbs.	3/8-24	9-7/8"	13-7/8"	5-1/2	3/8"		14
45-100	Jaw/Jaw	To 5/16"	10,500 lbs.	4200 lbs.	1/2-20	11-1/2"	15-1/2"	6-1/2	1/2"	1	0
47-100	Jaw/Jaw	To 3/8"	14,800 lbs.	5900 lbs.	5/8-18	14-1/2"	19"	7-3/4	5/8"	3	4

\*\* Jaw with "T" Toggle Construction. All others have bronze toggle nuts to prevent galling under high load conditions.

*Click here to contact American Rigging Supply, Inc.*

**Open Body Turnbuckles - Jaw and Machine Swage**



Specifications & Data

CAT. NO.	TYPE	WIRE SIZE	APPROX. BREAKING STRENGTH	SAFE WORKING LOAD	THREAD SIZE	ADJUSTMENT	BODY LENGTH	PIN DIA	WT.	
									lb	oz
42-113**	Jaw/Swage	3/32"	2,500 lbs	1000 lbs.	1/4-28	3"	4-5/8	1/4"		4
42-114**	Jaw/Swage	1/8"	2,500 lbs	1000 lbs.	1/4-28	3"	4-5/8	1/4"		4
42-115**	Jaw/Swage	5/32"	2,500 lbs	1000 lbs.	1/4-28	3"	4-5/8	1/4"		4
43-115**	Jaw/Swage	5/32"	4,000 lbs.	1600 lbs	5/16-24	3-5/8"	5-1/2	5/16"		7
43-116**	Jaw/Swage	3/16"	4,000 lbs.	1600 lbs	5/16-24	3-5/8"	5-1/2	5/16"		7
44-116**	Jaw/Swage	3/16"	7,000 lbs	2800 lbs.	3/8-24	4"	5-1/2	3/8"		12
44-117**	Jaw/Swage	7/32"	7,000 lbs	2800 lbs.	3/8-24	4"	5-1/2	3/8"		12
44-118**	Jaw/Swage	1/4"	7,000 lbs	2800 lbs.	3/8-24	4"	5-1/2	3/8"		12
45-108	Jaw/Swage	1/4"	10,500 lbs	3500 lbs.	1/2-20	4-1/8"	6-1/2	1/2"		9
45-109	Jaw/Swage	9/32"	10,500 lbs	3500 lbs.	1/2-20	4-1/8"	6-1/2	1/2"		9
45-110	Jaw/Swage	5/16"	10,500 lbs	4200 lbs.	1/2-20	4-1/8"	6-1/2	1/2"		9
47-110	Jaw/Swage	5/16"	14,800 lbs	4200 lbs.	5/8-18	5"	7-3/4	5/8"	3	8
47-112	Jaw/Swage	3/8"	14,800 lbs	5900 lbs.	5/8-18	5"	7-3/4	5/8"	3	8

\*\* Jaw with "T" Toggle Construction. All others have bronze toggle nuts to prevent galling under high load conditions.



photo courtesy of Catalina Yachts



photo courtesy of J Boats



**Stainless Steel Tubular Turnbuckles - Jaw and Jaw  
Check Nut Locking**

**All T-316 Stainless!**

**Specifications & Data**

CAT. NO.	TYPE	WIRE SIZE	APPROX. BREAKING STRENGTH	SAFE WORKING LOAD	THREAD SIZE	PIN TO PIN LENGTH		BODY LENGTH	PIN DIA	WT.	
						Closed	Open			lb	oz
03-110**	Jaw/Jaw	To 3/32"	1,000 lbs	400 lbs.	10-32	6-3/8"	8-7/8"	3-1/2	3/16"		2.5
04-100	Jaw/Jaw	To 5/32"	2,500 lbs.	1000 lbs	1/4-28	8"	11"	4-1/2	1/4"		5
04-110**	Jaw/Jaw	To 5/32"	2,500 lbs	1000 lbs.	1/4-28	8"	11"	4-1/2	1/4"		5
Δ 05-110**	Jaw/Jaw	To 3/16"	4,000 lbs.	1600 lbs.	5/16-24	9"	12-3/4"	5-1/8	5/16"		8
Δ 06-110**	Jaw/Jaw	To 1/4"	7,000 lbs.	2800 lbs.	3/8-24	9-1/2"	13-3/4"	5-5/8	3/8"		14
Δ 09-100-2	Jaw/Jaw	To 5/16"	10,500 lbs.	4200 lbs.	1/2-20	12"	16-3/4"	7	1/2"	1	12
Δ 10-100-2	Jaw/Jaw	To 3/8"	14,800 lbs.	5900 lbs.	5/8-18	14"	19"	8-5/8	5/8"	3	10

\*\*Jaw with "T" Toggle Construction. All others have bronze toggle nuts to prevent galling under high load conditions.

Δ Available with Bronze Rods on special order. Add-1 to catalog number, no price increase.

**Click here to contact American Rigging Supply, Inc.**

**Stainless Steel Tubular Turnbuckles - Classic Jaw & Machine Swage**

Check Nut Locking

**Specifications & Data**

TECH TIP - Pin size = jaw width See page 39 for full specs of toggles

CAT. NO.	TYPE	WIRE SIZE	APPROX. BREAKING STRENGTH	SAFE WORKING LOAD	THREAD SIZE	ADJUSTMENT	BODY LENGTH	PIN DIA	WT. lb oz	
03-112*	Jaw/Swage	*1/16"	1,000 lbs	400 lbs.	10-32	2-1/2"	3-1/2	3/16"		2
03-113*	Jaw/Swage	3/32"	1,000 lbs	400 lbs.	10-32	2-1/2"	3-1/2	3/16"		2
04-103*	Jaw/Swage	3/32"	2,500 lbs	1000 lbs.	1/4-28	3"	4-1/2	1/4"		4
04-104	Jaw/Swage	1/8"	2,500 lbs	1000 lbs	1/4-28	3"	4-1/2	1/4"		4
04-105	Jaw/Swage	5/32"	2,500 lbs	1000 lbs	1/4-28	3"	4-1/2	1/4"		4
04-113**	Jaw/Swage	3/32"	2,500 lbs	1000 lbs.	1/4-28	3"	4-1/2	1/4"		4
04-114**	Jaw/Swage	1/8"	2,500 lbs	1000 lbs.	1/4-28	3"	4-1/2	1/4"		4
04-115**	Jaw/Swage	5/32"	2,500 lbs	1000 lbs.	1/4-28	3"	4-1/2	1/4"		4
05-115**	Jaw/Swage	5/32"	4,000 lbs	1600 lbs.	5/16-24	3-3/4"	5-1/8	5/16"		7
05-116**	Jaw/Swage	3/16"	4,000 lbs	1600 lbs.	5/16-24	3-3/4"	5-1/8	5/16"		7
06-116**	Jaw/Swage	3/16"	7,000 lbs	2800 lbs.	3/8-24	4-1/4"	5-5/8	3/8"		12
06-117**	Jaw/Swage	7/32"	7,000 lbs	2800 lbs.	3/8-24	4-1/4"	5-5/8	3/8"		12
06-118**	Jaw/Swage	1/4"	7,000 lbs	2800 lbs.	3/8-24	4-1/4"	5-5/8	3/8"		12
09-108-2	Jaw/Swage	1/4"	10,500 lbs	3500 lbs.	1/2-20	4-1/8"	7	1/2"	1	9
09-109-2	Jaw/Swage	9/32"	10,500 lbs	3500 lbs.	1/2-20	4-1/8"	7	1/2"	1	9
09-110-2	Jaw/Swage	5/16"	10,500 lbs	4200 lbs.	1/2-20	4-1/8"	7	1/2"	1	9
10-110-2	Jaw/Swage	5/16"	14,800 lbs	4200 lbs.	5/8-18	5"	8-5/8	5/8"	3	2
10-112-2	Jaw/Swage	3/8"	14,800 lbs	5900 lbs.	5/8-18	5"	8-5/8	5/8"	3	2



NOTE: The 03 & 04 series come standard with L.H. upper terminal. All other series have R. H. The 04 series is available with R. H. upper terminal. To order add -12 to the catalog number.

\*\*Jaw with "T" Toggle Construction. All others have bronze toggle nuts to prevent galling under high load conditions.

\*Swage with 3/32" die.

**All T-316 Stainless!**



photo courtesy of Morris Yachts