

Unit 3C

Supplied By:
American Rigging Supply, Inc.

Soft Spectra® line attachments are used for the halyard, head and tack and eliminate the need for heavy welded lugs and shackles



	Rod Ø	Clevis Pin Ø
	-22, -30 (9.5, 11.1 mm)	3/4", 7/8" (19.1, 22.2 mm)
Headstay Length	Standard 75'9" (23 m); max 83' (25.3 m)	
Part No.	Description	
1129	Carbon furling system — specify rod and clevis pin	
Optional Parts		
1125	7.25' (2.21 m) Carbon foil/connector kit	

Unit 3.25C

	Rod Ø	Clevis Pin Ø
	-40 (12.7 mm)	7/8", 1" (22.2, 25.4 mm)
Headstay Length	Standard 75'10" (23.1 m); max 90'4" (27.5 m)	
Part No.	Description	
1130	Carbon furling system — specify rod and clevis pin	
Optional Parts		
1125	7.25' (2.21 m) Carbon foil/connector kit	
1116	14.5' (4.42 m) Carbon foil/connector kit	

Optional Parts



- 1116
- 1117
- 1118
- 1119
- 1125
- 1126
- 1127
- 1128

Unit 3.5C

	Rod Ø	Clevis Pin Ø
	-48 (14.3 mm)	7/8", 1", 1 1/8" (22.2, 25.4, 28.6 mm)
Headstay Length	Standard 76'2" (23.2 m); max 97'11" (29.8 m)	
Part No.	Description	
1131	Carbon furling system — specify rod and clevis pin	
Optional Parts		
1126	7.25' (2.21 m) Carbon foil/connector kit	
1117	14.5' (4.42 m) Carbon foil/connector kit	

Unit 4C

	Rod Ø	Clevis Pin Ø
	-60, -76 (16.8, 17.9 mm)*	1 1/4" (31.8 mm)
Headstay Length	Standard 91'7" (27.9 m); max 113'4" (34.5 m)	
Part No.	Description	
1132	Carbon furling system — specify rod and clevis pin	
Optional Parts		
1127	7.25' (2.21 m) Carbon foil/connector kit	
1118	14.5' (4.42 m) Carbon foil/connector kit	

*Continuous rod only. If rod is sectional, order 4.5

Unit 4.5C

	Rod Ø	Clevis Pin Ø
	-76, -91, -115 (17.9, 19.5, 22.2 mm)	1 1/4", 1 3/8", 1 9/16" (31.8, 34.9, 39.7 mm)
Headstay Length	Standard 106'4" (32.4 m); max 128' (39 m)	
Part No.	Description	
1133	Carbon furling system — specify rod and clevis pin	
Optional Parts		
1128	7.25' (2.21 m) Carbon foil/connector kit	
1119	14.5' (4.42 m) Carbon foil/connector kit	



Call for availability.