

WIRE BLOCKS, SHEAVE BOXES & UPRIGHT LEAD BLOCKS

Supplied By; American Rigging Supply, Inc.

www.americanriggingsupply.com



FEATURES

- ▶ Wire blocks have purpose designed narrow sheaves and grooves.

APPLICATIONS

- ▶ Wire blocks suit halyards, vang and backstay applications.

- ▶ Upright lead blocks are a low profile solution for leading lines to cleats or jammers.
- ▶ Sheave boxes are ideal for applications where lines (rope or wire) need to be led through decks, bulkheads or spars minimising friction and chafing.

MATERIALS

- ▶ U.V. stabilised Acetal sheaves.
- ▶ Nylatron® sheaves (wire blocks and sheave boxes).
- ▶ Grade 316 stainless steel cheeks.

PRODUCT No.	DESCRIPTION	SHEAVE DIAM. mm	(in.)	MAX. WIRE mm	(in.)	M.W.L. kg	(lb)	B.L. kg	(lb)	WEIGHT g	(oz)									
Wire Blocks																				
RF103	Single block, tubular rivet head, removable sheave	45	(1 3/4)	4	(5/32)	850	(1870)	1700	(3740)	88	(3.1)									
RF104	Single block, ferrule top, removable sheave	45	(1 3/4)	4	(5/32)	850	(1870)	1700	(3740)	80	(2.8)									
RF418	Single block, tubular rivet head	25	(1)	3	(1/8)	450	(990)	900	(1980)	40	(1.4)									
RF418C	Single block, removable clevis pin head	25	(1)	3	(1/8)	450	(990)	900	(1980)	39	(1.4)									
RF468	Single block, ferrule top, removable sheave	32	(1 1/4)	3	(1/8)	450	(990)	900	(1980)	33	(1.1)									
RF560	Single block, ferrule eye	19	(3/4)	3	(1/8)	250	(550)	500	(1100)	20	(0.7)									
RF667	Single block, loop top	19	(3/4)	2	(3/32)	200	(440)	400	(880)	20	(0.7)									
PRODUCT No.	SHEAVE DIAM. mm	MAX. ROPE mm	MAX. WIRE mm	A mm	B mm	C mm	D mm	M.W.L. kg	B.L. kg	WEIGHT g										
Sheave Boxes																				
RF452	22	(7/8)	3	(1/8)	3	(1/8)	25.5	(1)	26	(1)	7.5	(5/16)	5	(3/16)	160	(350)	320	(700)	30	(1.1)
RF31712	30	(1 3/16)	8	(5/16)	4	(5/32)	44	(1 3/4)	27	(1 1/16)	14	(9/16)	5	(3/16)	375	(830)	800	(1760)	45	(1.6)
RF41712	40	(1 9/16)	10	(3/8)	5	(3/16)	54	(2 1/8)	33	(1 5/16)	17	(11/16)	5	(3/16)	500	(1100)	1000	(2200)	75	(2.6)
RF51712	50	(2)	12	(1/2)	5	(3/16)	62	(2 7/16)	42	(1 5/8)	21	(13/16)	5	(3/16)	800	(1760)	1500	(3300)	145	(5.1)
PRODUCT No.	SHEAVE DIAM. mm	MAX. ROPE mm	MAX. WIRE mm	M.W.L. kg	B.L. kg	WEIGHT g														
Upright Lead Blocks																				
RF453	22	(7/8)	3	(1/8)	3	(1/8)	160	(350)	320	(700)	30	(1.1)								
RF568	19	(3/4)	5	(3/16)	-	-	250	(550)	500	(1100)	20	(0.7)								
RF569	19	(3/4)	8	(5/16)	-	-	250	(550)	500	(1100)	20	(0.7)								
RF917	19	(3/4)	8	(5/16)	-	-	250	(550)	500	(1100)	20	(0.7)								
RF919	29	(1 3/32)	6	(1/4)	-	-	600	(1320)	1200	(2640)	50	(1.8)								
RF2379	13	(19/32)	5	(3/16)	-	-	250	(550)	500	(1100)	20	(0.7)								