

American Rigging Supply, Inc.



### FEATURES

- ▶ Removable screw-in padeyes are ideal for attaching blocks which may be removed when not in use or while cruising. A threaded plug remains in the base section when the top

plate is removed to prevent dirt and grit from entering the threads.

### MATERIALS

- ▶ Grade 316 stainless steel.
- ▶ Duplex SD100 stainless steel (RF2429).

PRODUCT No.		A mm (in.)	B mm (in.)	C mm (in.)	D mm (in.)	B.L. kg (lb)	WEIGHT g (oz)
<b>Padeyes</b>							
RF2432-09		14 (9/16)	9.0 (11/32)	55 (2 5/32)	6 (1/4)	4000 (8820)	105 (3.7)
RF2433-09	Removable, screw-in	14 (9/16)	9.0 (11/32)	55 (2 5/32)	6 (1/4)	4000 (8820)	285 (10.1)
RF2430-06		16 (5/8)	6.4 (1/4)	51 (2)	6.5 (1/4)	2500 (5510)	124 (4.4)
RF2430-08		16 (5/8)	7.9 (5/16)	57 (2 1/4)	8 (5/16)	3500 (7720)	127 (4.5)
RF2429	Investment cast	19 (3/4)	8.0 (5/16)	71 (2 13/16)	10 (13/32)	9000 (19840)	220 (7.8)
RF2432-10		19 (3/4)	10.0 (13/32)	72 (2 27/32)	8 (5/16)	5000 (11020)	190 (6.7)
RF2433-10	Removable, screw-in	19 (3/4)	10.0 (13/32)	72 (2 27/32)	8 (5/16)	5000 (11020)	550 (19.4)
RF2432-12		22.5 (7/8)	12.0 (15/32)	85 (3 11/32)	10 (13/32)	6000 (13230)	390 (13.8)
RF2433-12	Removable, screw-in	22.5 (7/8)	12.0 (15/32)	85 (3 11/32)	10 (15/32)	8000 (17640)	1025 (36.2)
RF2432-16		30 (1 3/16)	16.0 (5/8)	100 (3 15/16)	12 (15/32)	9000 (19840)	580 (20.5)
RF2433-16	Removable, screw-in	30 (1 3/16)	16.0 (5/8)	100 (3 15/16)	12 (15/32)	9000 (19840)	1980 (69.8)
<b>Pad Eyes - Diamond Base</b>							
RF529*	Incl. nylon mounting pad	18 (23/32)	8.0 (5/16)	75 x 51 (3 x 2)	6.4 (1/4)	2000 (4400)	100 (4.0)
RF415	Incl. nylon mounting pad	21 (13/16)	8.0 (5/16)	75 x 51 (3 x 2)	5.0 (3/16)	1000 (2200)	75 (2.7)
RF44	Incl. nylon mounting pad	22 (7/8)	11.0 (7/16)	94 x 60 (3 11/16 x 2 3/8)	6.7 (1/4)	2000 (4400)	130 (4.6)
RF416		25 (1)	6.4 (1/4)	83 x 35 (3 1/4 x 1 3/8)	4.8 (3/16)	800 (1760)	40 (1.4)
* Turned U-Bolt with a pad eye base. Thread size is 6.4mm (1/4" UNC). Suits maximum deck thickness of 22mm (7/8")							
<b>Saddles - Narrow</b>							
RF134		36.5 (1 7/16)	5 (3/16)	4.8 (3/16)	14 (9/16)	-	5 (0.2)
RF134A	Countersunk holes	36.5 (1 7/16)	5 (3/16)	4.8 (3/16)	14 (9/16)	-	5 (0.2)
RF498		27 (1 1/16)	4 (5/32)	3.5 (1/8)	10 (13/32)	-	4 (0.1)
RF528		44 (1 23/32)	8 (5/16)	7 (9/32)	12 (15/32)	-	25 (0.9)
RF1054		60 (2 3/8)	8 (5/16)	5.5 (7/32)	18 (23/32)	-	35 (1.2)
RF1055		45 (1 25/32)	6 (1/4)	7 (9/32)	16 (5/8)	-	15 (0.5)
<b>Saddles - Flared Top</b>							
RF94		27.5 (1 3/32)	5 (3/16)	9 (11/32)	6 (1/4)	-	3 (0.1)
RF94A		40 (1 9/16)	5 (3/16)	6 (1/4)	5 (3/16)	-	3 (0.1)
RF148		41 (1 5/8)	6 (1/4)	12 (15/32)	15 (9/32)	-	8 (0.3)
RF291		32 (1 1/4)	5 (3/16)	9 (11/32)	13 (1/2)	-	7 (0.2)
RF5013NC		38 (1 1/2)	5 (3/16)	12.5 (1/2)	15 (19/32)	-	8 (0.3)
RF5023NC		51 (2)	6 (1/4)	14 (9/16)	18 (3/4)	-	11 (0.4)
<b>Saddles - Ferrule Eye</b>							
RF499		8.0 (5/16)	4.0 (5/32)	28.0 (1 1/8)	4.0 (5/32)	-	4 (0.1)
RF1058		10.0 (13/32)	5.0 (3/16)	36.0 (1 7/16)	5.0 (3/16)	-	9 (0.3)
RF1057		12.5 (1/2)	6.0 (1/4)	45.0 (1 3/4)	6.0 (1/4)	-	18 (0.6)
RF1056		16.0 (5/8)	8.0 (15/16)	60.0 (2 3/8)	8.0 (5/16)	-	40 (1.4)

