

Supplied By; American Rigging Supply, Inc.

www.americanriggingsupply.com



Acetal - Ball Bearing

Acetal - Oilite® Bearing

Acetal - Solid Bearing

Glass Reinforced Nylon

Nylatron®

Aluminium

Brass

ACETAL SHEAVES

- ▶ U.V. resistant Acetal sheaves.
- ▶ Choice of bearings
- ▶ Acetal ball bearings - minimum friction under moderate loads.
- ▶ Solid bearing - high strength and durability, utilizing the self-lubricating properties of Acetal.
- ▶ Oilite® bearing – Oil impregnated self-lubricating bearing for highest load applications.

GLASS REINFORCED NYLON SHEAVES

- ▶ Glass reinforced for greater strength and abrasion resistance.

NYLATRON® SHEAVES

- ▶ Cast partially cross-linked polyamide compound, modified with a MoS2 filler for lubrication and to minimize wear.
- ▶ Suitable for use with wire or rope.

GLASS REINFORCED NYLON SHEAVES

- ▶ Glass reinforced for greater strength and abrasion resistance.

ALUMINIUM SHEAVES

- ▶ Self-lubricating Oilite® bearing.
- ▶ Anodised aluminium for corrosion resistance and high strength.
- ▶ Suitable for use with wire or rope.

BRASS SHEAVES

- ▶ Nickel plated for corrosion wear resistance.
- ▶ Suitable for use with wire or rope.

PRODUCT No.	DIAM.		BORE		WIDTH		MAX. ROPE		MAX. WIRE		BLOCK SUITED
	mm	(in.)	mm	(in.)	mm	(in.)	mm	(in.)	mm	(in.)	
ACETAL – Ball Bearing											
RF1020	28	(1 1/8)	5.0	(3/16)	11.1	(7/16)	6.0	(1/4)	–	–	–
RF1766	38	(1 1/2)	8.0	(5/16)	15.0	(19/32)	10.0	(3/8)	–	–	–
RF1767	50.4	(2)	8.0	(5/16)	14.3	(9/16)	10.0	(3/8)	–	–	–
ACETAL – Oilite® Bearing											
RF431	73	(2 7/8)	12.7	(1/2)	21.2	(27/32)	14.0	(9/16)	–	–	Series 75 AP
ACETAL – Solid Bearing											
RF1741	19	(3/4)	6.6	(1/4)	6.4	(1/4)	6	(1/4)	–	–	–
RF1743	19	(3/4)	8.1	(11/32)	9.5	(3/8)	6	(1/4)	–	–	–
RF578	25	(1)	6.5	(1/4)	9.5	(3/8)	6	(1/4)	–	–	–
RF128	29	(1 1/8)	7.9	(5/16)	15.1	(19/32)	12	(1/2)	–	–	–
RF129	29	(1 1/8)	6.6	(1/4)	9.9	(3/8)	8	(5/16)	–	–	–
RF1749	29	(1 1/8)	11.3	(7/16)	15.6	(19/32)	12	(1/2)	–	–	–
RF251	38	(1 1/2)	6.5	(1/4)	9.9	(3/8)	8	(5/16)	–	–	–
RF41000	38	(1 1/2)	8.2	(11/32)	14.2	(9/16)	10	(13/32)	–	–	Series 40 AP
RF1006	38	(1 1/2)	12.7	(1/2)	15.5	(19/32)	12	(1/2)	–	–	Series 38 Deck Organisers
RF1751	38	(1 1/2)	8.2	(11/32)	10.2	(13/32)	6	(1/4)	–	–	–
RF1759	50	(1 15/16)	8.1	(11/32)	15.6	(19/32)	14	(9/16)	–	–	–
RF127	55	(2 3/16)	11.3	(7/16)	15.6	(19/32)	12	(1/2)	–	–	–
RF130	55	(2 3/16)	8.5	(11/32)	14.2	(9/16)	6	(1/4)	–	–	–
RF437	60	(2 3/8)	11.4	(7/16)	19.0	(3/4)	16	(5/8)	–	–	Series 60 AP
RF1765	66	(2 5/8)	8.2	(11/32)	15.1	(15/32)	5	(3/16)	–	–	–
GLASS REINFORCED NYLON											
PNP98JR	75	(2 15/16)	12.0	(15/32)	15.8	(19/32)	10	(3/8)	–	–	–
PNP98KR	100	(3 15/16)	12.0	(15/32)	19.0	(3/4)	12	(1/2)	–	–	–
PNP98NR	150	(5 7/8)	12.5	(1/2)	19	(3/4)	14	(9/16)	–	–	–
NYLATRON®											
RF131	25	(31/32)	6.6	(1/4)	6.4	(1/4)	–	–	5	(3/16)	–
RF30000HL	30	(1 3/16)	8.1	(5/16)	11.4	(7/16)	8	(5/16)	3	(1/8)	Series 30 HL
RF40000HL	40	(1 1/2)	8.1	(5/16)	13.4	(17/32)	10	(3/8)	4	(5/32)	Series 40 HL
RF132	45	(1 3/4)	8.0	(5/16)	9.5	(3/8)	–	–	6	(1/4)	RF103,104
RF50000HL	50	(1 31/32)	10.2	(13/32)	18	(23/32)	12	(1/2)	5	(3/16)	Series 50 HL
ALUMINIUM											
RF436	62	(2 7/16)	11.2	(7/16)	19.0	(3/4)	12.0	(1/2)	6	(1/4)	Series 60 AP
RF2855	76	(3)	9.6	(3/8)	15.6	(19/32)	12.0	(1/2)	6	(1/4)	–
RF1060	76	(3)	16.0	(5/8)	22.2	(7/8)	14.0	(9/16)	18	(23/32)	–
RF2857	102	(4)	11.3	(7/16)	18.2	(23/32)	14.0	(9/16)	8	(5/16)	–
BRASS											
RF429	57	(2 1/4)	8.2	(5/16)	10.2	(13/32)	–	–	8	(5/16)	–
RF580	57	(2 1/4)	9.8	(3/8)	15.8	(5/8)	–	–	6	(1/4)	–
RF579	74	(2 15/16)	12.9	(1/2)	12.7	(1/2)	–	–	6	(1/4)	RF69, 69S, 71