



Photo © 2004 Stephen Whitesell

## Splicing Tools & Kits



The Samson Splice Training Kit comes complete with a fid, pusher, instruction manual and a length of double braid rope.



The Samson Splicing Kit comes with 5 aluminum tubular fids (size range 1/4" through 1/2" diameter).

Size Diameter	Put-Up	Pack Lbs.	Units Per Pack
1/4" Fid	1 each	0.6 lbs.	12
5/16" Fid	1 each	1.2 lbs.	12
3/8" Fid	1 each	1.8 lbs.	12
7/16" Fid	1 each	2.4 lbs.	12
1/2" Fid	1 each	2.4 lbs.	12
9/16" Fid	1 each	3.0 lbs.	6
5/8" Fid	1 each	3.0 lbs.	6
3/4" Fid	1 each	6.0 lbs.	6
7/8" Fid	1 each	9.0 lbs.	6
1" Fid	1 each	12.0 lbs.	6
Small Pusher	1 each	2.4 lbs.	12
Large Pusher	1 each	2.4 lbs.	6
Selma Fids	set of 5	0.5 lbs.	1
Splice Training	1 each	12.0 lbs.	6
Splicing Kit	1 kit	9.6 lbs.	12



## Lash-It!

A single braid made from Dyneema® fiber with Samthane urethane coating. Offers high strength to weight ratio. It is stronger than steel, floats and will not absorb water. Multiple uses – it's the sailor's duct tape.

Size Diameter	Spool Put-Up	Average Strength	Net Wet. Lbs.
1.75 mm	180' Tube	400 lbs.	0.22 lbs.
1.75 mm	600' Spool	400 lbs.	0.72 lbs.



## MFP Floatline

2-in-1® Braid with a multifilament polypropylene cover and floating core. Yellow with red ID.

Size Diameter	Spool Put-Up	Average Strength	Net Wet. Lbs.
1/4"	600'	1,700 lbs.	8.6 lbs.
3/8"	600'	2,300 lbs.	16.2 lbs.
1/2"	600'	3,700 lbs.	28.8 lbs.



## Hollow Braid Polypropylene

UV Stabilized, mono-filament, polypropylene. Easy to splice. Floats. Color: Green.

Size Diameter	Spool Put-Up	Average Strength	Net Wet. Lbs.
3/16"	600'	750 lbs.	3.6 lbs.
1/4"	600'	1,200 lbs.	6.6 lbs.
5/16"	600'	1,700 lbs.	9.6 lbs.
3/8"	600'	2,600 lbs.	13.8 lbs.
1/2"	600'	4,300 lbs.	22.2 lbs.



## Accessory Cord

With a polyester cover and nylon core, Samson's Accessory Cord has excellent flexibility, knotting and strength characteristics for a smooth running, torque-free cord.

Size Diameter	Spool Put-Up	Average Strength	Net Wet. Lbs.
2 mm	300'	230 lbs.	0.6 lbs.
3 mm	300'	600 lbs.	1.5 lbs.
4 mm	300'	1,000 lbs.	2.4 lbs.
5 mm	300'	1,200 lbs.	4.2 lbs.
6 mm	300'	2,200 lbs.	5.4 lbs.
7 mm	300'	2,800 lbs.	6.9 lbs.
8 mm	300'	3,500 lbs.	9.0 lbs.
9 mm	300'	4,300 lbs.	11.4 lbs.