

Supplied By American Rigging Supply, Inc.



TERMINAL TO TERMINAL INSULATORS

Part Number	Sta-Lok Number	Wire Size	Breaking Load	Overall Length	Overall Diameter
SLIN07	143-55	7/32"	9000	7-1/2	1-3/8
SLIN08	143-06	1/4"	9000	7-1/2	1-3/8
SLIN09	143-07	9/32"	15000	8	1-1/2
SLIN10	143-08	5/16"	15000	8	1-1/2
SLIN12	143-10	3/8"	21900	9	1-5/8
SLIN14	143-11	7/16"	29607	11-3/16	2
SLIN16	143-12	1/2"	29607	11-3/16	2



INSULATOR BODY ONLY

Part Number	Sta-Lok Number	Wire Size	Breaking Load
SLINB07	206-55	7/32"	9000
SLINB08	206-06	1/4"	9000
SLINB09	206-07	9/32"	15000
SLINB10	206-08	5/16"	15000
SLINB12	206-10	3/8"	21900
SLINB14	206-11	7/16"	29607
SLINB16	206-12	1/2"	29607

TERMINAL END WITH WEDGE & FORMER



Part Number	Sta-Lok Number	Wire Size
SLTE07	211-55	7/32"
SLTE08	211-06	1/4"
SLTE09IN*	211-07	9/32"
SLTE10	211-08	5/16"
SLTE12	211-10	3/8"
SLTE14	211-11	7/16"
SLTE16	211-12	1/2"

*Fits 5/16 body.

For More Information, Contact American Rigging Supply, Inc.



STA-LOK Insulators

Gaining world-wide recognition for high quality and total reliability

In 1973 STA-LOK introduced a new design of wire rope terminal which so simplified the termination of wire rope that it became essential equipment for both the amateur and professional rigger. Thirty years on, the STA-LOK terminal is used by professionals around the world, and has gained world-wide recognition for high quality and total reliability.

STA-LOK insulators are a range of high quality, high performance wire rope fittings for 1 x 19, 7 x 7, 7 x 19, compacted and Dyform wire ropes. The main body of the insulator consists of an ingenious stainless steel assembly. The whole is embedded in a black weatherproof nylon injection moulding

Electrical Properties	
Impedance Measurement @ 15 MHz	Capacitance 16 Pf Resistance 400 K
D.C Leakage Resistance @ 30Kv	Greater than 10 G Ohms
Voltage Proof Test	Withstands 30 Kv applied for 2 hours without breakdown

Hand fitted or machine swaged

Insulators are available in a range of different end fittings for wire sizes 5mm to 12mm and 3/16" to 1/2" including the STA-LOK self fit terminal or swage ends, as required. The STA-LOK insulator is stronger than the wire rope. It will work under constant load and variable shock loading. In all situations the STA-LOK insulator has proven totally reliable.

Reusable

Manufactured from 316 stainless steel grade 1.4401, All STA-LOK terminals are reusable* requiring no servicing, providing long life and very low maintenance costs.

** A new wedge component must be used.*