


Loose Bails

Supplied By: American Rigging Supply, Inc.



Bottom View of Loose Bail

Individual bails available for use as standoffs, termination fittings or in special rigging applications.

SB = Standard Bail
LB = Large Bail

SWIVEL TYPE	A in (mm)	B in (mm)	WORK LOAD lb (kg)	BREAKING STRENGTH lb (kg)
T5 SB	.398 (10.1)	14.6	2,500 (1,136)	5,000 (2,273)
T5 LB	.398 (10.1)	.712 (18.1)	2,500 (1,136)	5,000 (2,273)
T8 SB	.398 (10.1)	.685 (17.4)	4,000 (1,818)	8,000 (3,636)
T8 LB	.398 (10.1)	.838 (21.3)	4,000 (1,818)	8,000 (3,636)
T12 SB	.476 (12.1)	.889 (22.6)	6,000 (2,727)	12,000 (5,455)
T12 LB	.476 (12.1)	.974 (24.7)	6,000 (2,727)	12,000 (5,455)
T20 SB	.638 (16.2)	1.074 (27.3)	10,000 (4,545)	20,000 (9,091)
T20 LB	.638 (16.2)	1.215 (30.9)	10,000 (4,545)	20,000 (9,091)
T30 SB	.795 (20.2)	1.460 (37.1)	15,000 (6,818)	30,000 (13,630)
T30 LB	.795 (20.2)	1.560 (39.6)	15,000 (6,818)	30,000 (13,630)
T40 SB	.960 (24.4)	1.671 (42.4)	20,000 (9,091)	40,000 (18,182)
T40 LB	.960 (24.4)	2.083 (52.9)	20,000 (9,091)	40,000 (18,182)
T50 SB	1.200 (30.5)	2.433 (61.8)	25,000 (11,364)	50,000 (22,727)
T50 LB	1.200 (30.5)	3.472 (88.2)	25,000 (11,364)	50,000 (22,727)




INDIVIDUAL LINKED BAILS

All sizes and configurations available for special rigging applications



Swivels



STANDARD/STANDARD

STANDARD/STANDARD

LARGE/LARGE

SWIVEL TYPE	A in (mm)	B in (mm)	C in (mm)	D in (mm)	E in (mm)	WEIGHT oz (gm)	WORK LOAD lb (kg)	BREAKING STRENGTH lb (kg)
T5 SB/SB	9/16 (14.2)	9/16 (14.2)	1 1/32 (13.5)	9/16 (14.2)	2 3/8 (60.3)	1.8 (51)	2,500 (1,136)	5,000 (2,273)
T5 SB/LB	9/16 (14.2)	9/16 (14.2)	1 3/16 (20.6)	7/8 (22.2)	2 3/4 (69.9)	2.2 (63)	2,500 (1,136)	5,000 (2,273)
T5 LB/LB	7/8 (22.2)	7/8 (22.2)	1 3/16 (20.6)	7/8 (22.2)	3 1/16 (77.8)	2.6 (74)	2,500 (1,136)	5,000 (2,273)
T8 SB/SB	1 1/16 (17.5)	2 1/32 (16.7)	1 9/32 (15.1)	2 1/32 (16.7)	2 13/16 (71.4)	2.6 (74)	4,000 (1,818)	8,000 (3,636)
T8 SB/LB	1 1/16 (17.5)	2 1/32 (16.7)	3 1/32 (24.6)	1 (25.4)	3 3/16 (81)	3.3 (94)	4,000 (1,818)	8,000 (3,636)
T8 LB/LB	1 1/16 (27)	1 (25.4)	3 1/32 (24.6)	1 (25.4)	3 5/8 (92)	4.1 (117)	4,000 (1,818)	8,000 (3,636)
T12 SB/SB	2 5/32 (19.8)	3/4 (19.1)	3/4 (19.1)	3/4 (19.1)	3 1/4 (83)	4.4 (125)	6,000 (2,727)	12,000 (5,455)
T12 SB/LB	2 5/32 (19.8)	3/4 (19.1)	1 1/8 (28.6)	1 3/16 (30.2)	3 3/4 (95)	6.0 (170)	6,000 (2,727)	12,000 (5,455)
T12 LB/LB	1 3/16 (30.2)	1 3/16 (30.2)	1 1/8 (28.6)	1 3/16 (30.2)	4 9/32 (109)	7.6 (216)	6,000 (2,727)	12,000 (5,455)
T20 SB/SB	1 3/32 (27.8)	3 1/32 (24.6)	1 5/16 (23.8)	3 1/32 (24.6)	4 1 1/32 (110)	9.9 (281)	10,000 (4,545)	20,000 (9,091)
T20 SB/LB	1 3/32 (27.8)	3 1/32 (24.6)	1 3/8 (34.9)	1 1/2 (38.1)	4 1 3/16 (122)	12.2 (347)	10,000 (4,545)	20,000 (9,091)
T20 LB/LB	1 1/2 (38.1)	1 1/2 (38.1)	1 3/8 (34.9)	1 1/2 (38.1)	5 5/16 (135)	14.4 (409)	10,000 (4,545)	20,000 (9,091)
T30 SB/SB	1 1/4 (31.8)	1 1/4 (31.8)	1 13/16 (30.2)	1 1/4 (31.8)	5 1/2 (140)	20 (568)	15,000 (6,818)	30,000 (13,636)
T30 SB/LB	1 1/4 (31.8)	1 1/4 (31.8)	1 3/4 (44.4)	1 29/32 (48.4)	6 1/4 (159)	27.6 (784)	15,000 (6,818)	30,000 (13,636)
T30 LB/LB	1 13/16 (30.2)	1 29/32 (48.4)	1 3/4 (44.4)	1 29/32 (48.4)	7 (178)	33.2 (943)	15,000 (6,818)	30,000 (13,636)
T40 SB/SB	1 2 1/32 (42.1)	1 2 1/32 (42.1)	1 1/2 (38.1)	1 2 1/32 (42.1)	7 (178)	40.3 (1,144)	20,000 (9,091)	40,000 (18,182)
T40 SB/LB	1 2 1/32 (42.1)	1 2 1/32 (42.1)	2 1 7/32 (62.7)	2 1 7/32 (64.3)	8 3/32 (206)	56.1 (1,595)	20,000 (9,091)	40,000 (18,182)
T40 LB/LB	2 1 7/32 (64.3)	2 1 7/32 (64.3)	2 1 5/32 (62.7)	2 1 7/32 (64.3)	9 3/16 (233)	71.8 (2,039)	20,000 (9,091)	40,000 (18,182)
T50 SB/SB	2 1/8 (53.9)	2 (50.8)	2 7/32 (56.4)	2 (50.8)	9 1/16 (230)	92.5 (2,626)	25,000 (11,364)	50,000 (22,727)
T50 SB/LB	2 1/8 (53.9)	2 (50.8)	3 5/16 (84.1)	3 1/4 (82.5)	10 7/16 (265)	127.6 (3,624)	25,000 (11,364)	50,000 (22,727)
T50 LB/LB	3 3/16 (81.3)	3 1/4 (82.5)	3 5/16 (84.1)	3 1/4 (82.5)	11 5/8 (295)	153.5 (4,360)	25,000 (11,364)	50,000 (22,727)

SB = Standard Bail, LB = Large Bail